

Technical data	EVG 24V36W	EVG 24V18W
Lamp type	36W, T8, 1200 mm	18W, T8, 600mm
Rated voltage DC	24 V	24V
Operating voltage range	16,8 V - 32,0 V	16,8V-32,0V
Input current consumption	1,3 A - 2,3 A	0,65A-1,15A
Operating frequency of the lamp	ca. 44 kHz	ca.51 kHz
Operating mode	Dauerbetrieb	Continuous operation
Reverse polarity protection	yes	yes
Temperature class according to En50155	T3	T3
Ambient temperature range	-25°C ... +70	-25°C ... +70°C
Railway vehicles - DC-supplied ECGs for fluorescent lamps	EN50311:2003	EN50311:2003
EMC testing	EN50121-3-2, EN55011	EN50121-3-2, EN55011
Vibration and impact testing	EN61373:1999	EN61373:1999
Connections	Terminal strips with confirmation push-button	Terminal strips with confirmation push-button
Dimensions L x W x H	260 mm x 40 mm x 31 mm	260mm x 40mm x 31mm
Weight	approx. 0,25 kg	approx. 0,25 kg
Manufacturer:	protronic Innovative Steuerungselektronik GmbH Grimmaische Str. 92 04828 Bennewitz district Pausitz	☎(+49) 34383 - 6315-0 ☎(+49) 34383 - 6315-50 ✉ info@protronic-gmbh.de